

AS 504

TIRE SIZE	10.0/75 - 15.3
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	264	RIM REC	9.00
OD (MM)	785	ECE	E4-106R-001823
SLR (MM)	360	PR	18
RC (MM)	2404	SRI	360

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	7.10
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180
10 DW	2170
25 DW	1845
30 DW	1735
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.