DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 50

TIRE SIZE	**29.5 R 25**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	PALA CARICATRICE
VERSIONE	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	208 A2

DIMENSIONI US STANDARD

CODICE USA	94037230	**RIM REC**	25.00/3.5
OD (IN)	74.8	**TRA CODE**	L5
SLR (IN)	33.9	**STAR RATING**	★
RC (IN)	225.3		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73
5	34200	35300	37500	38600	39700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..