


FORESTMAX

TIRE SIZE	650/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAKTOR / SKOTARE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	172 A8 ; 186 A2



DIMENSIONER US STANDARD

USA CODE	94076437	RC (IN)	215.2
SW (IN)	25.4	RIM REC	DW 20 B
OD (IN)	71.3	RIM ALT	DW21B; DW23B
SLR (IN)	32.8	ECE	E11-106R-0011042

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	46	49	52
30	6720	7250	7760	8510	9180	9630	9960	10500	10870	11250	11650	12120	12500
25	7470	8060	8620	9450	10210	10700	11070	11670	12070	12500	12940	13480	13890
20	8000	8630	9240	10120	10920	11450	11850	12500	12930	13390	13860	14430	14870
15	8290	8950	9580	10490	11330	11880	12290	12960	13400	13890	14360	14970	15420
12	9190	9910	10600	11620	12550	13160	13610	14350	14850	15380	15920	16580	17080
10	10010	10800	11560	12660	13680	14340	14840	15640	16180	16770	17350	18070	18620
5	11260	12150	13010	14240	15390	16130	16690	17590	18210	18850	19510	20310	20940
5 FORESTRY SERVICE	-	-	-	-	-	-	-	-	-	-	-	-	17080
0 FORESTRY SERVICE	-	-	-	-	-	-	-	-	-	-	-	-	31940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.