

## TR 135

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | <b>16.9 - 34</b>   |
| <b>UM</b>           | US STANDARD        |
| <b>CONSTRUCTION</b> | BIAS               |
| <b>MACHINERY</b>    | TRACTOR / ANHÄNGER |
| <b>VERSION</b>      | STANDARD           |
| <b>TIRE TYPE</b>    | TT                 |
| <b>LI/SS</b>        | 140 A8             |



### ABMESSUNGEN US STANDARD

|                 |          |                |        |
|-----------------|----------|----------------|--------|
| <b>USA-CODE</b> | 94003723 | <b>RC (IN)</b> | 188.7  |
| <b>SW (IN)</b>  | 16.9     | <b>RIM REC</b> | W 15 L |
| <b>OD (IN)</b>  | 62.4     | <b>RIM ALT</b> | W 14 L |
| <b>SLR (IN)</b> | 28.7     | <b>PR</b>      | 12     |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>34</b> |
| 25               | 5510      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.