

# PL 801

<b>TIRE SIZE</b>	<b>8.25 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ANCINHO ROTATIVO / CEIFEIRA / EMPILHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / EMPILHADOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94007295	<b>RIM ALT</b>	6.0; 7.0
<b>SW (IN)</b>	9.3	<b>PR</b>	12
<b>OD (IN)</b>	33.6		
<b>RIM REC</b>	6.5		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>102</b>
<b>15 LOAD WHEEL</b>	8600
<b>15 STEER WHEEL</b>	6615
<b>5 OTHER VEHICLES</b>	8600
<b>15 OTHER VEHICLES</b>	6615
<b>STATIC SIDE LOADER</b>	9985

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.