

FLOTATION TR 675

TIRE SIZE	500/60 - 22.5
UM	IS STANDARD
CONSTRUCTION	❖ BIAS
MACHINERY	MAQUINARIA AGRÍCOLA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B



DIMENSIONES IS STANDARD

SW (MM)	515	RIM REC	AG 16.00
OD (MM)	1181	RIM ALT	15.00; 17.00
SLR (MM)	542	ECE	E4-106R-002314
RC (MM)	3604	PR	12

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	2.00	2.40
10 FR	4390	5195	5775
20 FR	3950	4675	5200
30 FR	3510	4155	4620
40 FR	3135	3710	4125
50 FR	2820	3340	3750
10 DW	3085	3645	4060
20 DW	2780	3280	3655
30 DW	2470	2920	3250
40 DW	2205	2605	2900
50 DW	1985	2345	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.