


MULTIMAX MP 527

TIRE SIZE	460/70 R 24 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARGADORA COMPACTA / ELEVADOR TELESCÓPICO / CARGADORA COMPACTA / ELEVADOR TELESCÓPICO
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	159 A8/B



DIMENSIONES US STANDARD

CÓDIGO USA	94052097	RC (IN)	149.6
SW (IN)	18.3	RIM REC	DW 15 L
OD (IN)	49.4	RIM ALT	DW 14 L; DW 16 L
SLR (IN)	22.6	ECE	E11-106R-002983

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	4630	5500	6270	7140	8010	8590	9640	-	-
25	4630	5500	6270	7140	8010	8590	9640	-	-
20	4960	5900	6720	7650	8580	9190	10330	-	-
15	5150	6120	6970	7940	8900	9550	10710	-	-
5 CYC.	5650	6960	8180	9410	10710	11650	13170	13900	14470
STATIC	8660	10660	12540	14430	16420	17870	20190	21310	22190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.