


# TR 315

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 23X8.50 - 12  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS                            |
| <b>MACHINERY</b>    | ATTREZZI AGRICOLI / MACCHINA PER<br>IL RACCOLTO DI FRUTTETI /<br>SCAVAFOSSI / MIETITREBBIA /<br>ATTREZZI AGRICOLI |
| <b>VERSIONE</b>     | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSIONI IS STANDARD

|                 |      |                |                                   |
|-----------------|------|----------------|-----------------------------------|
| <b>SW (MM)</b>  | 205  | <b>RIM REC</b> | 7 JA; 7.00 I - 55; I - 70; I - 90 |
| <b>OD (MM)</b>  | 575  | <b>ECE</b>     | E4-106R-002178                    |
| <b>SLR (MM)</b> | 258  | <b>PR</b>      | 6                                 |
| <b>RC (MM)</b>  | 1668 |                |                                   |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 15                | 650         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.