


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 600/50 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRIDARE / TANKBIL / SLÄPVAGN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 159 D |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1170 | ECE | E11-106R-005992 |
| SLR (MM) | 518 | SRI | 550 |
| RC (MM) | 3533 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 70 | 1455 | 1635 | 2035 | 2315 | 2670 | 3030 | 3310 | 3630 | 3985 |
| 65 | 1600 | 1795 | 2235 | 2540 | 2935 | 3325 | 3635 | 3985 | 4375 |
| 50 | 1935 | 2175 | 2705 | 3075 | 3550 | 4025 | 4395 | 4820 | 5295 |
| 40 | 2175 | 2440 | 3035 | 3455 | 3990 | 4525 | 4940 | 5415 | 5950 |
| 25 | 2525 | 2840 | 3530 | 4015 | 4635 | 5260 | 5740 | 6295 | 6915 |
| 10 | 2875 | 3230 | 4020 | 4570 | 5280 | 5985 | 6540 | 7170 | 7875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.