


# RT 853

<b>TIRE SIZE</b>	<b>520/85 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1849	<b>RIM ALT</b>	DW 18 L ; DD 16 L
<b>SLR (MM)</b>	830	<b>ECE</b>	E4-106R-001483
<b>RC (MM)</b>	5592	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	2135	2480	2830	3180	3530	3875
40	2135	2480	2830	3180	3530	3875
30	2285	2660	3030	3405	3780	4150
10 LT	2860	3325	3795	4260	4730	5195
10 HT	2285	2660	3030	3405	3780	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.