

AGRIMAX RT 855

TIRE SIZE	520/85 R 46
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 A8/B



DIMENSIONS US STANDARD

CODE USA	94040544	RC (IN)	248.4
SW (IN)	20.3	RIM REC	DW 16 L ; W 16 A ; W 16 L ; DD 16
OD (IN)	81.7	RIM ALT	DW 18 L ; W 18 L ; W 18 A
SLR (IN)	38.0	ECE	E4-106R-001494

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	35	41	46	52	58
30	5160	6000	6840	7680	8530	9370	10750	11750	12750	13610	14330
25	5160	6000	6840	7680	8530	9370	10750	11750	12750	13610	14330
20	5520	6430	7330	8230	9140	10030	11500	12580	13650	14560	15330
5 LT	6910	8040	9170	10300	11430	12550	14410	15740	17080	18240	19200
5 HT	5520	6430	7330	8230	9140	10030	11500	12580	13650	14560	15330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.