


AGRIMAX FORCE

TIRE SIZE	IF 710/75 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	178 D



DIMENSIONER IS STANDARD

SW (MM)	716	RIM REC	DW 25 B
OD (MM)	1929	RIM ALT	DW 23 B
SLR (MM)	870	ECE	E11-106R-003017
RC (MM)	5775	SRI	900

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3205	3685	4230	4775	5320	5865	6415	6825
FROM 65 TO 40	3525	4050	4650	5250	5850	6450	7050	7500
30	3665	4210	4835	5460	6080	6705	7330	7800
20	3805	4370	5020	5670	6315	6965	7610	8100
10	4475	5140	5905	6665	7425	8190	8950	9525
UPTO 30 CYC	4580	5265	6045	6825	7605	8385	9165	9750
UPTO 15 CYC	5460	6275	7205	8135	9065	9995	10925	11625
UPTO 10 CYC	5990	6885	7905	8925	9945	10965	11985	12750
10 HT	3665	4210	4835	5460	6080	6705	7330	7800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.