

# FLOTATION RIB 774

<b>TIRE SIZE</b>	550/60 - 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	✠ BIAS
<b>MACHINERY</b>	ERNTMASCHINE / ANHÄNGER / ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	160 A8/156 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94006601	<b>RC (IN)</b>	146.7
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	48.8	<b>ECE</b>	E11-106R-005941
<b>SLR (IN)</b>	21.3	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	30
5 FR	11410	12690	13890
10 FR	10260	11420	12500
20 FR	9130	10150	11110
25 FR	8150	9060	9920
30 FR	7330	8160	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.