

## AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>650/65 R 42</b>                       |
| <b>UM</b>        | IS STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | STANDARD                                 |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 165 D ; 168 A8                           |



### DIMENSIONS IS STANDARD

|                 |      |                |                   |
|-----------------|------|----------------|-------------------|
| <b>SW (MM)</b>  | 645  | <b>RIM REC</b> | DW 20 B           |
| <b>OD (MM)</b>  | 1913 | <b>RIM ALT</b> | DW 21 B ; DW 23 B |
| <b>SLR (MM)</b> | 878  | <b>ECE</b>     | E4-106R-000625    |
| <b>RC (MM)</b>  | 5810 | <b>SRI</b>     | 925               |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|------|------|------|------|------|------|------|------|
| <b>65</b>    | 2475 | 2885 | 3245 | 3605 | 3970 | 4275 | 4740 | 5150 |
| <b>50</b>    | 2600 | 3030 | 3410 | 3790 | 4170 | 4495 | 4980 | 5410 |
| <b>40</b>    | 2690 | 3140 | 3530 | 3920 | 4315 | 4650 | 5155 | 5600 |
| <b>30</b>    | 2845 | 3320 | 3735 | 4150 | 4565 | 4920 | 5455 | 5925 |
| <b>10 LT</b> | 3315 | 3870 | 4355 | 4835 | 5320 | 5735 | 6355 | 6905 |
| <b>10 HT</b> | 2845 | 3320 | 3735 | 4150 | 4565 | 4920 | 5455 | 5925 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.