

FLOTATION 558

TIRE SIZE	400/55 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINĂ DE RECOLTARE / CISTERNĂ / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	144 A8/140 B
LI/SS FREE ROLLING	156 A8/152 B



DIMENSIUNI US STANDARD

USA CODE	94058501	RC (IN)	121.4
SW (IN)	15.9	RIM REC	AG 11.75
OD (IN)	40.2	RIM ALT	12.25; 13.00; AG 13.00
SLR (IN)	17.5	ECE	E11-106R-005351

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	67	70	73
5 FR	11760	12050	12350
10 FR	10580	10850	11110
20 FR	9400	9640	9880
25 FR	8400	8610	8820
30 FR	7560	7750	7830
5 DW	8220	8440	8640
10 DW	7410	7590	7780
20 DW	6580	6760	6910
25 DW	5870	6030	6170
30 DW	5290	5420	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.