


# RIDEMAX FL 615

<b>TIRE SIZE</b>	<b>VF 900/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ПРИЦЕП / АВТОЦИСТЕРНА / РАЗБРАСЫВАТЕЛЬ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	200 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	891	<b>RIM REC</b>	DW 30 B
<b>OD (MM)</b>	2115	<b>ECE</b>	E11-106R-0011504
<b>SLR (MM)</b>	929	<b>SRI</b>	975
<b>RC (MM)</b>	6445		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8
65	6860	7700	9380	10640	12320	14000
50	8030	9010	10975	12450	14415	16380
40	8850	9935	12105	13730	15895	18060
30	9675	10860	13230	15005	17375	19740
25	10020	11245	13695	15535	17990	20440
20	10430	11705	14260	16175	18730	21280
10	11255	12630	15385	17450	20205	22960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.