

AGRIMAXFACTOR

TIRE SIZE	620/70 R 42
UM	US STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 D ; 176 A8



ABMESSUNGEN US STANDARD

USA-CODE	94073634	RIM REC	DW 20 B
SW (IN)	24.6	RIM ALT	DW18L ; W18L
OD (IN)	76.2	ECE	E11-106R-007766
SLR (IN)	34.5	TRA CODE	R1W
RC (IN)	228.5	TREAD DEPTH (32nd)	71.82

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
40	5590	6590	7590	8450	9460	10320	11320	12180	13330	14330
30	5870	6920	7980	8880	9930	10840	11890	12800	14000	15050
25	6130	7230	8320	9270	10360	11310	12400	13350	14600	15700
20	6440	7580	8740	9730	10880	11870	13030	14010	15330	16480
5 LT	7500	8840	10180	11330	12680	13830	15180	16320	17870	19200
5 HT	6440	7580	8740	9730	10880	11870	13030	14010	15330	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.