


# AW 09

<b>TIRE SIZE</b>	<b>260/70 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	114 A8
<b>LI/SS FREE ROLLING</b>	126 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94037841	<b>RC (IN)</b>	86.9
<b>SW (IN)</b>	10.6	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	29.6	<b>ECE</b>	E4-106R-000373
<b>SLR (IN)</b>	13.2		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	5250
15 FR	4460
20 FR	4200
25 FR	3750
5 DW	3640
15 DW	3100
20 DW	2910
25 DW	2600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.