


# AGRIMAX SPARGO

**VF 380/85 R 34**

|                     |  |
|---------------------|--|
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAKTÖR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 160 D  |



## UNDEFINED IS STANDARD

|                 |      |                |                    |
|-----------------|------|----------------|--------------------|
| <b>SW (MM)</b>  | 380  | <b>RIM REC</b> | W 13 A             |
| <b>OD (MM)</b>  | 1500 | <b>RIM ALT</b> | W 12               |
| <b>SLR (MM)</b> | 678  | <b>ECE</b>     | E11-106R-009071-01 |
| <b>RC (MM)</b>  | 4514 | <b>SRI</b>     | 725                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  |
|---------------|------|------|------|------|------|------|------|------|------|------|------|
| 70            | 2455 | 2745 | 3000 | 3165 | 3285 | 3410 | 3535 | 3705 | 3870 | 3995 | 4160 |
| FROM 65 TO 40 | 2655 | 2970 | 3240 | 3420 | 3555 | 3690 | 3825 | 4005 | 4185 | 4320 | 4500 |
| 30            | 2705 | 3030 | 3305 | 3490 | 3625 | 3765 | 3905 | 4085 | 4270 | 4410 | 4590 |
| 20            | 2760 | 3090 | 3370 | 3560 | 3695 | 3840 | 3980 | 4165 | 4355 | 4495 | 4680 |
| 10            | 2920 | 3265 | 3565 | 3765 | 3910 | 4060 | 4210 | 4405 | 4605 | 4755 | 4950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.