


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 650/65 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 169 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94059102 | RC (IN) | 212.1 |
| SW (IN) | 25.6 | RIM REC | DW 23 B |
| OD (IN) | 71.3 | RIM ALT | DW 21 B |
| SLR (IN) | 31.4 | ECE | E11-106R-005022 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|--------------------------------------|-------|-------|-------|-------|-------|-------|
| 45 | 6500 | 7670 | 8720 | 9770 | 10690 | 11630 |
| FROM 40 TO 25 | 7150 | 8430 | 9590 | 10740 | 11760 | 12800 |
| 20 | 7290 | 8600 | 9780 | 10950 | 11990 | 13040 |
| 12 | 7430 | 8760 | 9960 | 11150 | 12220 | 13290 |
| 5 | 7860 | 9270 | 10550 | 11810 | 12930 | 14060 |
| *UPTO 5 CYC WITH FRONT LOADER | 10010 | 11810 | 13430 | 15020 | 16460 | 17900 |
| 5 HT | 7290 | 8600 | 9780 | 10950 | 11990 | 13040 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.