


# AS 504

<b>TIRE SIZE</b>	7.5L - 15
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	97 A8
<b>LI/SS FREE ROLLING</b>	109 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	210	<b>RIM REC</b>	6 LB
<b>OD (MM)</b>	765	<b>RIM ALT</b>	5 K; 5½ J; 5½ K
<b>SLR (MM)</b>	354	<b>ECE</b>	E11-106R-004238
<b>RC (MM)</b>	2280	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	1440
25 FR	1225
30 FR	1155
40 FR	1030
10 DW	1020
25 DW	870
30 DW	820
40 DW	730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.