


AW 711

380/55 R 16.5

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / UYGULAMALI MAKINE / BIÇERDÖVER / UYGULAMALI MAKINE
VERSION	STUBBLE RESISTANT
TIRE TYPE	TL
	150 A8/B



UNDEFINED US STANDARD

USA CODE	94044757	RC (IN)	98.4
SW (IN)	14.2	RIM REC	12
OD (IN)	32.7	RIM ALT	11.75
SLR (IN)	14.6	ECE	E4-106R-001393

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73
30	2220	2890	3550	4070	4730	5400	5760	6360	6940	7400
25	2220	2890	3550	4070	4730	5400	5760	6360	6940	7400
20	2490	3230	3980	4560	5300	6050	6460	7120	7780	8280
15	2650	3440	4230	4840	5630	6430	6870	7570	8280	8800
10	2800	3640	4480	5130	5960	6800	7270	8010	8760	9310
5	3110	4030	4970	5690	6620	7550	8070	8900	9720	10340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.