

EARTHMAX SR 53



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 53

EARTHMAX SR 53 is an All Steel radial tyre specially designed for loaders, dozers and low profile dump trucks (LPDT) operating in severe rocky conditions, including underground operations and scrap yards. The deep L-5 tread and the cut-resistant compound provide an extended wear life in addition to excellent traction and stability. In case of underground mine application, consult your servicing dealer or BKT representative.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	20.5 R 25	TL	L5	*	186 A2	17.00/2.0	-	0	535	1550	705	4666	78	CR
	29.5 R 25	TL	L5	*	208 A2	25.00/3.5	-	0	770	1912	859	5755	103	CR
	23.5 R 25	TL	L5	**	201 A2	19.50/2.5	-	0	604	1666	758	5015	83,5	CR
	29.5 R 25	TL	L5	**	-	25.00/3.5	-	0	770	1912	859	5755	103	CRC UMS

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES				
							
L5	A2	274 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
17.5 R 25	TL	L5	**	182 A2	14.00/1.5	-	0	435	1400	637	4214	65,5	CR
23.5 R 25	TL	L5	**	-	19.50/2.5	-	0	604	1666	758	5015	83,5	CRC UMS
17.5 R 25	TL	L5	*	176 A2	14.00/1.5	-	0	435	1400	637	4214	65,5	CR
29.5 R 25	TL	L5	**	216 A2	25.00/3.5	-	0	770	1912	859	5755	103	CR
26.5 R 25	TL	L5	*	202 A2	22.00/3.0	-	0	680	1788	800	5376	95	CR
26.5 R 25	TL	L5	**	209 A2	22.00/3.0	-	0	680	1788	800	5376	95	CR
26.5 R 25	TL	L5	***	214 A2	22.00/3.0	-	0	680	1788	800	5376	95	CR
17.5 R 25	TL	L5	***	188 A2	14.00/1.5	-	0	435	1400	637	4214	65,5	CR
23.5 R 25	TL	L5	*	195 A2	19.50/2.5	-	0	604	1666	758	5015	83,5	CR

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES				
							
							
A2	274 kg						

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.D. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
NEW	17.5 R 25	TL	L5	**	-	14.00/1.5	-	0	435	1400	637	4214	65,5	CRC UMS
	26.5 R 25	TL	L5	**	-	22.00/3.0	-	0	680	1788	800	5376	95	CRC UMS
	20.5 R 25	TL	L5	**	193 A2	17.00/2.0	-	-	535	1550	705	4666	78	CR
Ø29"	29.5 R 29	TL	L5	***	223 A2	25.00/3.5	24.00/3.5	0	755	2015	905	6059	102	CR
	29.5 R 29	TL	L5	**	-	25.00/3.5	24.00/3.5	0	755	2015	905	6059	102	CRC UMS
	29.5 R 29	TL	L5	**	218 A2	25.00/3.5	24.00/3.5	0	755	2015	905	6059	102	CR
Ø33"	35/65 R33	TL	L5	**	-	28.00/3.5	-	0	910	2063	915	6215	92	CRC UMS
	35/65 R33	TL	L5	**	224 A2	28.00/3.5	-	0	910	2063	915	6215	92	CR
	35/65 R 33 (LPDT)	TL	L5	**	-	28.00/3.5	-	0	910	2063	915	6215	92	CRC UMS

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES				
							
							
A2	274 kg						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	35/65 R 33	TL	L5	***	229 A2	28.00/3.5	-	0	910	2063	915	6215	92	CR
Ø39"	45/65 R 39	TL	L5	**	242 A2	36.00/4.5	32.00/4.5	0	1100	2577	1118	7747	110	CR
Ø45"	45/65 R 45	TL	L5	***	250 A2	36.00/4.5	-	0	1125	2730	1211	8224	112	CR
	45/65 R 45	TL	L5	**	245 A2	36.00/4.5	-	0	1125	2730	1211	8224	112	CR
Ø51"	50/65 R51	TL	L5	**	253 A2	40.00/4.5	-	0	1240	3090	1371	9309	128	CR
Ø57"	60/80 R 57	TL	L5	**	274 A2	47.00/5.0	47.00/6.0	0	1515	3930	1743	11840	118	CR
NEW	55/80 R57	TL	L5	**	268 A2	44.00/5.0	-	-	1400	3740	1642	11185	120	CR

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES				
							
A2	L5	274 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES			PERFORMANCES				
A2	L5	274 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026