

# AS 504

|                           |                  |
|---------------------------|------------------|
| <b>TYRE SIZE</b>          | <b>7.50 - 20</b> |
| <b>UM</b>                 | US STANDARD      |
| <b>CONSTRUCTION</b>       | ⊠ BIAS           |
| <b>MACHINERY</b>          | IMPLEMENTS       |
| <b>VERSION</b>            | STANDARD         |
| <b>TYRE TYPE</b>          | TT               |
| <b>LI/SS DRIVE WHEEL</b>  | 103 A8           |
| <b>LI/SS FREE ROLLING</b> | 116 A8           |



## DIMENSIONS US STANDARD

|                 |          |                |                        |
|-----------------|----------|----------------|------------------------|
| <b>USA CODE</b> | 94019373 | <b>RC (IN)</b> | 106.1                  |
| <b>SW (IN)</b>  | 8.2      | <b>RIM REC</b> | 5.50 F                 |
| <b>OD (IN)</b>  | 35.6     | <b>RIM ALT</b> | 4.50 E; 6.00 F; 5.00 F |
| <b>SLR (IN)</b> | 16.6     | <b>ECE</b>     | E4-106R-002636         |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 46   |
|-----------|------|
| 5 FR      | 3860 |
| 15 FR     | 3260 |
| 20 FR     | 3090 |
| 25 FR     | 2760 |
| 5 DW      | 2700 |
| 15 DW     | 2290 |
| 20 DW     | 2160 |
| 25 DW     | 1930 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.