


MULTIMAX MP 529



TIRE SIZE	400/70 R 20 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SOLLEVATORE TELESOPICO
VERSIONE	STEEL BELTED
TIRE TYPE	TL
LI/SS	149 A8/B

DIMENSIONI US STANDARD

CODICE USA	94512737	RC (IN)	130.5
SW (IN)	16.3	RIM REC	13
OD (IN)	42.9	RIM ALT	12 SDC;13SDC;14
SLR (IN)	19.7	ECE	E11-106R-0010769

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	52	58	61	64
30	3420	4020	4630	5240	5840	6500	7160	-	-
25	3420	4020	4630	5240	5840	6500	7160	-	-
20	3660	4320	4990	5670	6330	7000	7670	-	-
15	3810	4500	5190	5890	6570	7260	7960	-	-
5 CYC.	4210	5150	6080	7010	7950	8880	9820	10300	10760
STATIC	6460	7890	9330	10760	12190	13620	15060	15770	16490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.