


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 240/70 R 16 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 107 A8 ; 107 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 244 | RIM REC | W8 |
| OD (MM) | 742 | RIM ALT | W9 |
| SLR (MM) | 343 | ECE | E11-106R-006942 |
| RC (MM) | 2226 | SRI | 350 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 |
|------------|-----|-----|-----|------|------|
| 50 | 545 | 675 | 730 | 860 | 975 |
| 40 | 545 | 675 | 730 | 860 | 975 |
| 30 | 585 | 725 | 785 | 985 | 1045 |
| 20 | 675 | 835 | 900 | 1135 | 1200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.