


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 600/60 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94053360	<b>RC (IN)</b>	173.4
<b>SW (IN)</b>	23.4	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	58.5	<b>RIM ALT</b>	DW 18 L; DW 21 B
<b>SLR (IN)</b>	25.6	<b>ECE</b>	E11-106R-002979

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4670	5460	6220	6990	7750	8520
<b>FROM 40 TO 25</b>	5150	6000	6830	7680	8520	9370
20	5250	6110	6970	7830	8690	9560
12	5350	6230	7100	7980	8850	9740
5	5650	6590	7520	8440	9370	10310
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7210	8390	9570	10750	11930	13120
5 HT	5250	6110	6970	7830	8690	9560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.