


# EARTHMAX SR 33

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>335/80 R 20</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | UNIVERSAL VEHICLE  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 150 K  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94059478 | <b>RIM REC</b> | 11              |
| <b>OD (IN)</b>  | 41.2     | <b>ECE</b>     | E11-54R-0016679 |
| <b>SLR (IN)</b> | 18.3     |                |                 |
| <b>RC (IN)</b>  | 123.8    |                |                 |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>94</b> |
| 68               | 7400      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.