


AGRIMAX FORCE

IF 650/85 R 42

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	180 D



UNDEFINED US STANDARD

USA CODE	94046904	RC (IN)	252.0
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	85.6	ECE	E4-106R-001832
SLR (IN)	38.0	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7540	8660	9940	11230	12510	13800	15080	16050
FROM 40 TO 25	8290	9520	10930	12350	13760	15170	16580	17600
20	8620	9900	11360	12830	14300	15770	17240	18340
12	8950	10280	11810	13330	14850	16380	17900	19050
5	10530	12090	13880	15670	17460	19260	21050	22400
UPTO 20 CYC	10770	12380	14210	16050	17880	19710	21550	22930
UPTO 10 CYC	12840	14760	16940	19140	21320	23500	25690	27340
UPTO 5 CYC	14090	16180	18580	20990	23380	25780	28170	29980
5 HT	8620	9900	11360	12830	14300	15770	17240	18340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.