DATA SHEET

PRINTED ON
23-04-2026

FLOTATION 648

TIRE SIZE	**650/65 - 30.5**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	167 A8/163 B
LI/SS FREE ROLLING	179 A8/175 B

DIMENSIUNI US STANDARD

USA CODE	94006465	**RC (IN)**	194.3
SW (IN)	26.4	**RIM REC**	AG 20.00
OD (IN)	65.4	**ECE**	E4-106R-001550
SLR (IN)	28.0	**PR**	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
5 FR	21260	22620	23920
10 FR	19140	20360	21530
20 FR	17010	18100	19140
25 FR	15190	16160	17080
30 FR	13670	14540	15210
5 DW	14960	15910	16820
10 DW	13460	14320	15130
20 DW	11960	12730	13460
25 DW	10680	11360	12010
30 DW	9610	10230	10750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..