


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 460/85 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 145 A8/B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 475 | RIM REC | W 16 L |
| OD (MM) | 1544 | RIM ALT | W 14 L ; W 15 L |
| SLR (MM) | 680 | ECE | E4-106R-000774 |
| RC (MM) | 4562 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1595 | 1860 | 2120 | 2380 | 2640 | 2900 |
| 40 | 1595 | 1860 | 2120 | 2380 | 2640 | 2900 |
| 30 | 1710 | 1990 | 2270 | 2550 | 2830 | 3105 |
| 10 LT | 2140 | 2490 | 2840 | 3190 | 3540 | 3890 |
| 10 HT | 1710 | 1990 | 2270 | 2550 | 2830 | 3105 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.