


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>480/80 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	489	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1890	<b>RIM ALT</b>	DD 16 L ; W 16 L
<b>SLR (MM)</b>	857	<b>ECE</b>	E4-106R-001481
<b>RC (MM)</b>	5629	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1900	2210	2520	2830	3140	3450
40	1900	2210	2520	2830	3140	3450
30	2035	2365	2700	3030	3365	3695
10 LT	2545	2960	3380	3795	4210	4625
10 HT	2035	2365	2700	3030	3365	3695

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.