

# FLOTATION 648

<b>TYRE SIZE</b>	<b>650/65 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	162 A8/158 B
<b>LI/SS FREE ROLLING</b>	174 A8/170 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94006458	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	26.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	65.4	<b>ECE</b>	E11-106R-004558
<b>SLR (IN)</b>	28.0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	22	23	25
<b>5 FR</b>	19210	19950	20680
<b>10 FR</b>	17290	17960	18610
<b>20 FR</b>	15370	15960	16540
<b>25 FR</b>	13720	14250	14770
<b>30 FR</b>	12360	12830	13230
<b>5 DW</b>	13620	14150	14660
<b>10 DW</b>	12270	12730	13190
<b>20 DW</b>	10900	11320	11730
<b>25 DW</b>	9730	10110	10470
<b>30 DW</b>	8760	9090	9370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.