


# AS 504

<b>TIRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	88 A8
<b>LI/SS FREE ROLLING</b>	100 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94037308	<b>RC (IN)</b>	80.7
<b>SW (IN)</b>	7.4	<b>RIM REC</b>	4.5
<b>OD (IN)</b>	26.9	<b>ECE</b>	E11-106R-003382
<b>SLR (IN)</b>	12.2	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	48
5 FR	2470
15 FR	2090
20 FR	1970
25 FR	1760
5 DW	1730
15 DW	1470
20 DW	1380
25 DW	1230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.