

EARTHMAX SR 33



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 33



EARTHMAX SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. The strong All Steel casing features excellent durability and resistance to snag and punctures.



SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION	
				REC RIM	ALT RIM						
											
Ø20"	335/80 R 20	TL	-	150 K	11	-	13.2	41.2	18.3	123.8	STD
	395/85 R 20	TL	-	168 J	10.00W	10.00HF	15.5	46.6	21.2	141.3	STD
	14.00 R 20	TL	-	164/160 J	10.0	10.00W 9.0	15.4	49.2	22.7	151.2	STD
	365/80 R 20 (14.5 R 20)	TL	-	152 K	11	-	14.2	43.1	19.5	130.6	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
			
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index