

XL GRIP (G3)



XL GRIP (G3)

XL GRIP (G-3) is a bias-ply tire for graders designed to minimize cuts and punctures in heavy-duty grading environments where exceptional traction is required.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø24"	14.00 - 24	TL	G3	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	365	1345	617	4002	30	STD
	13.00 - 24	TT	G3	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	350	1295	601	3872	30	STD
	14.00 - 24	TT	G3	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	365	1345	617	4002	30	STD
	16.00 - 24 (-)	TL	G3	16	-	10.00 VA SDC	-	0	432	1450	654	4289	32,5	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM)	OD	SLR	RC	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM		(mm)	(mm)	(mm)	(mm)		
														
	13.00 - 24	TL	G3	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	350	1295	601	3872	30	STD
Ø25"	18.00 - 25	TL	G3	40	-	13.00/2.5	15.00/2.5	0	510	1615	739	4780	31,5	STD
	18.00 - 25	TL	G3	32	-	13.00/2.5	15.00/2.5	0	510	1615	739	4780	31,5	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baktishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026