


# FARM 2000

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>16.9 - 28</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 139 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94002924 | <b>RC (IN)</b> | 171.3           |
| <b>SW (IN)</b>  | 16.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>  | 55.9     | <b>RIM ALT</b> | W 14 L          |
| <b>SLR (IN)</b> | 25.9     | <b>ECE</b>     | E11-106R-003627 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>36</b> |
| 25               | 5360      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.