

AGRIMAX RT 765

TIRE SIZE	280/70 R 16
UM	IS STANDARD
MACHINERY	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	112 A8/B



ABMESSUNGEN IS STANDARD

SW (MM)	282	RIM ALT	W 8 ; W 8 L ; W 10
OD (MM)	798	ECE	E4-106R-000633
SLR (MM)	356	SRI	380
RC (MM)	2370	TRA CODE	R1W
RIM REC	W 9	TREAD DEPTH (MM)	31,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	530	605	695	785	875	965	1045	1120
40	530	605	695	785	875	965	1045	1120
30	565	650	745	840	940	1035	1120	1200
10 LT	710	815	935	1055	1175	1295	1400	1505
10 HT	565	650	745	840	940	1035	1120	1200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.