


# AGRIMAX RT 855

**340/85 R 24**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
	125 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94043972	<b>RC (IN)</b>	139.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	46.8	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	20.9	<b>ECE</b>	E4-106R-000604

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2010	2340	2660	2990	3320	3640
25	2010	2340	2660	2990	3320	3640
20	2150	2500	2850	3210	3560	3900
5 LT	2690	3130	3570	4010	4450	4880
5 HT	2150	2500	2850	3210	3560	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.