


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>480/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	141 D ; 144 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94074792	<b>RC (IN)</b>	172.9
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	58.2	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (IN)</b>	26.4	<b>ECE</b>	E11-106R-008811

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	3130	3640	4140	4660	5170	5680
30	3280	3820	4350	4890	5430	5960
25	3430	3980	4540	5100	5670	6150
20	3600	4190	4770	5370	5950	6540
5 LT	4200	4880	5570	6250	6930	7620
5 HT	3600	4190	4770	5370	5950	6540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.