


AGRIMAX TERIS

TIRE SIZE	900/60 R 32 CHO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ERNTMASCHINE / BAUMWOLLERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	185 A8 ; 182 B



ABMESSUNGEN US STANDARD

USA-CODE	94040865	RC (IN)	227.4
SW (IN)	34.4	RIM REC	DW 27 B
OD (IN)	75.2	RIM ALT	DW 28 B; DW 30 B
SLR (IN)	34.4	ECE	E4-106R-001433

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	52	58
30	7440	8430	10580	11740	13060	14050	15380	16530	17610	18740
25	8190	9280	11640	12920	14370	15460	16920	18190	19170	20390
20	8760	9930	12470	13820	15390	16560	18110	19470	20510	21820
10 CYC	13510	15310	19210	21320	23720	25520	27920	30010	31630	33650
5 CYC	14740	16700	20950	23250	25870	27830	30460	32740	34510	36700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.