

# RIB 774 (A)

<b>TIRE SIZE</b>	250/65 - 14.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	☒ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	124 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	255	<b>RIM REC</b>	AG 8.00
<b>OD (MM)</b>	690	<b>RIM ALT</b>	6.75
<b>SLR (MM)</b>	303	<b>ECE</b>	E11-106R-003374
<b>RC (MM)</b>	1978	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.50
10 FR	2240
25 FR	1905
30 FR	1790
40 FR	1600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.