

AGRIMAX RT 765

TIRE SIZE	480/70 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	141 D



РАЗМЕРЫ US STANDARD

USA CODE	94062218	RC (IN)	172.1
SW (IN)	18.9	RIM REC	W 15 L
OD (IN)	58.2	RIM ALT	W 14 L; W 16 L
SLR (IN)	25.9	ECE	E11-106R-005522

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	3130	3640	4140	4660	5170	5680
30	3280	3820	4350	4890	5430	5960
25	3430	3980	4540	5100	5670	6220
20	3600	4190	4770	5370	5950	6540
5 LT	4200	4880	5570	6250	6930	7620
5 HT	3600	4190	4770	5370	5950	6540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.