


# TF 9090

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>9.00 - 16</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRATTORINO / TRATTORE / RIMORCHIO  |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 108 A8   |



## DIMENSIONI US STANDARD

|                   |          |                |                    |
|-------------------|----------|----------------|--------------------|
| <b>CODICE USA</b> | 94021338 | <b>RC (IN)</b> | 100.3              |
| <b>SW (IN)</b>    | 10.1     | <b>RIM REC</b> | W 8                |
| <b>OD (IN)</b>    | 33.7     | <b>RIM ALT</b> | 6.00 F; W 7; W 8 L |
| <b>SLR (IN)</b>   | 15.7     | <b>ECE</b>     | E4-106R-002669     |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>60</b> |
| 25               | 2400      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.