


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>340/80 R 18 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	143 A8 ; 138 D



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94048960	<b>RC (IN)</b>	117.3
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	11; 11 SDC; W 11
<b>OD (IN)</b>	39.4	<b>RIM ALT</b>	W 10; 12; 12 SDC
<b>SLR (IN)</b>	18.0	<b>ECE</b>	E11-106R-002987

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	51	58
40	2030	2500	2970	3380	3850	4320	4630	5200
30	2190	2700	3210	3660	4160	4660	5000	5620
25	2350	2890	3430	3900	4440	4980	5350	6010
20	2450	3010	3580	4070	4630	5200	5570	6250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.