

# AGRIMAX FORCE

|                  |                                                  |
|------------------|--------------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 710/75 R 42 CFO</b>                        |
| <b>UM</b>        | IS STANDARD                                      |
| <b>MACHINERY</b> | COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR |
| <b>VERSIÓN</b>   | STANDARD                                         |
| <b>TIRE TYPE</b> | TL                                               |
| <b>LI/SS</b>     | 181 D                                            |

## DIMENSIONES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 716  | <b>RIM REC</b> | DW 25 B         |
| <b>OD (MM)</b>  | 2133 | <b>RIM ALT</b> | DW 23 B         |
| <b>SLR (MM)</b> | 967  | <b>ECE</b>     | E11-106R-006490 |
| <b>RC (MM)</b>  | 6403 | <b>SRI</b>     | 1000            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0  | 1.2  | 1.4   | 1.6   | 2.0   | 2.4   |
|----------------------|------|------|------|------|-------|-------|-------|-------|
| <b>70</b>            | 3525 | 4050 | 4650 | 5255 | 5855  | 6455  | 7055  | 7505  |
| <b>FROM 65 TO 40</b> | 3875 | 4455 | 5115 | 5775 | 6435  | 7095  | 7755  | 8250  |
| <b>30</b>            | 4030 | 4630 | 5315 | 6005 | 6690  | 7375  | 8065  | 8580  |
| <b>20</b>            | 4185 | 4810 | 5520 | 6235 | 6945  | 7660  | 8375  | 8910  |
| <b>10</b>            | 4920 | 5655 | 6495 | 7330 | 8170  | 9010  | 9845  | 10475 |
| <b>UPTO 30 CYC</b>   | 5035 | 5790 | 6645 | 7505 | 8365  | 9220  | 10080 | 10725 |
| <b>UPTO 15 CYC</b>   | 6005 | 6905 | 7925 | 8950 | 9970  | 10995 | 12020 | 12785 |
| <b>UPTO 10 CYC</b>   | 6585 | 7570 | 8695 | 9815 | 10935 | 12060 | 13180 | 14025 |
| <b>10 HT</b>         | 4030 | 4630 | 5315 | 6005 | 6690  | 7375  | 8065  | 8580  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

