


AGRIMAX RT 955

| | |
|---------------------|--|
| | 270/80 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | UYGULAMALI MAKINE / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 131 A8/B |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 270 | RIM REC | W 9 |
| OD (MM) | 1225 | RIM ALT | W 8 ; W 10 |
| SLR (MM) | 569 | ECE | E11-106R-0011741 |
| RC (MM) | 3711 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 | 2 | 2.4 | 2.8 | 3.2 | 3.6 | 4 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 685 | 800 | 920 | 1035 | 1155 | 1250 | 1385 | 1465 | 1600 | 1740 | 1855 | 1950 |
| 40 | 685 | 800 | 920 | 1035 | 1155 | 1250 | 1385 | 1465 | 1600 | 1740 | 1855 | 1950 |
| 30 | 735 | 860 | 985 | 1110 | 1235 | 1340 | 1485 | 1570 | 1715 | 1865 | 1990 | 2090 |
| 10 | 1025 | 1200 | 1375 | 1555 | 1730 | 1875 | 2080 | 2195 | 2400 | 2605 | 2780 | 2925 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.