

AGRIMAX RT 855

TIRE SIZE	250/85 R 22
UM	US STANDARD
MACHINERY	PULVERIZADOR / VENDIMIADORA / TRACTOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	113 A8/B



DIMENSIONES US STANDARD

CÓDIGO USA	94062058	RIM ALT	W 7
SW (IN)	9.9	ECE	E11-106R-002973
OD (IN)	38.8	TRA CODE	R1W
SLR (IN)	17.8	TREAD DEPTH (32nd)	45.99
RC (IN)	116.7	TMPH (TM/H)	1
RIM REC	W 8		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.