

# FLOTATION 648

**550/45 - 22.5**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESI / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	154 A8/150 B
	166 A8/162 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	525	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1070	<b>ECE</b>	E4-106R-002046
<b>SLR (MM)</b>	488	<b>PR</b>	20
<b>RC (MM)</b>	3253		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.50	4.00
10 FR	6270	6860	7420
20 FR	5645	6175	6680
30 FR	5020	5490	5935
40 FR	4480	4900	5300
50 FR	4030	4410	4750
10 DW	4440	4860	5250
20 DW	3995	4370	4725
30 DW	3550	3885	4200
40 DW	3170	3470	3750
50 DW	2855	3125	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.