


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>540/70 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1366	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	611	<b>ECE</b>	E11-106R-002967
<b>RC (MM)</b>	4133	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2690	3195	3640	4145	4650	4985	5600	-	-
40	2690	3195	3640	4145	4650	4985	5600	-	-
30	2880	3420	3900	4440	4980	5340	5995	-	-
25	2990	3550	4045	4605	5165	5540	6220	-	-
10 CYC.	3280	4035	4750	5460	6220	6765	7645	8065	8400
STATIC	5025	6185	7280	8375	9535	10370	11725	12365	12880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.